



Skyliner® Technical Bulletin 008:
Skyliner® Safety (Slide) Clip and Banding System

Skyliner® System's unique Safety (Slide) Clip and Banding System is an integral part of the overall Skyliner® system. Installed properly, the Safety (Slide) Clip and Banding System allows the Skyliner® system to meet OSHA Standard 29 CFR 1926.502(c)(4)(i) for leading-edge fall protection.

The Safety Clip is ONLY to be installed on the banding 16" adjacent to interior frames. Safety banding is attached to the eave strut, using a Tek 2 fastener. Fasteners are placed in the center of the flange. The Safety (Slide) Clip is installed after the fabric is in place. The clip encompasses the Safety Banding and is designed to allow the Safety Banding to slide, should pressure be applied. Slide the Safety (Slide) Clip over the Safety Banding, and attach to each purlin, using a Tek 2 fastener. The Safety (Slide) Clip flange direction should alternate on each purlin and Safety Banding should freely slide in Safety (Slide) Clip.

Installing banding, safety banding and clips (adjacent to frames), BayBond™ adhesive, and Skyliner® fabric (on roll) according to Skyliner® Instruction Manual meets OSHA Standard 29 CFR 1926.502(c)(4)(i) for leading-edge fall protection.

**Questions? Contact your Bay District Manager,
call 844.999.7153 or visit www.SkylinerSystems.com.**

(Photo of Actual fabric)